

ADDITIVE	TECHNICAL DATA	CS-38
	RUST-OLEUM® ULTRAWEAR® ADDITIVE	

DESCRIPTION AND USES

Rust-Oleum® UltraWear® Additive is a specially refined blend of aluminum oxide to provide improved wear resistance of floor coatings. UltraWear Additive will also add slight surface texture to floor coatings and promote skid resistance of the dry coating.

APPEARANCE

Off white particles or granules

PRODUCT

SKU	DESCRIPTION
313898	UltraWear Additive

PACKAGING

One pound bags

RECOMMENDED COATINGS

Any floor coating with a dry film thickness of 8 mils or less

PRODUCT APPLICATION

The UltraWear Additive can be mixed directly into the coating. Use one pound of additive per gallon of coating. Stir the container frequently to ensure the additive does not settle out. Apply the coating by roller.

PHYSICAL PROPERTIES

		ULTRAWEAR ADDITIVE
Composition		Aluminum Oxide
Weight	Per Gallon	33.0 lbs.
	Per Liter	3.97 kg
Solids	By Weight	100%
	By Volume	100%
Volatile Organic Compounds		0
Shelf Life		5 years
Safety Information		For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.



Rust-Oleum Corporation
 11 Hawthorn Parkway
 Vernon Hills, Illinois 60061

Phone: 800-899-1729
www.rustoleum.com/industrial

Form: GDH-83
 Rev.: 081120