

• TRUSTED QUALITY SINCE 1921 •



**RUST-OLEUM®
HEAVY DUTY CLEANER**

DESCRIPTION AND USES

Rust-Oleum® Heavy Duty Cleaner is formulated to clean grease and oil stains on concrete surfaces prior to painting, staining, and sealing. Heavy Duty Cleaner is ideal for use on garage floors, basements, concrete driveways, sidewalks, porches, patios, and stairs.

PRODUCT

SKU	DESCRIPTION
N266001	Heavy Duty Cleaner

PACKAGING

946mL Plastic bottle

PRODUCT APPLICATION

SURFACE PREPARATION

Wipe up excess oil and grease spills. Scrape and sweep away dirt and loose contaminants on surface.

PRODUCT APPLICATION (cont.)

MIXING

Use Rust-Oleum® Heavy Duty Cleaner at full strength to clean tough stains. Dilute 1:4 (1 quart [32 oz.] Degreaser in 1 gallon [128 oz.] of water) for general purpose cleaning. To keep your painted floor looking great, dilute 1:16 (1 cup [8 oz.] Cleaner in 1 gallon [128 oz.] of water). Stir diluted solution thoroughly. Avoid splashing.

APPLICATION

Wet the surface first by spraying with a garden hose. Apply the product full strength for tough stains or diluted for general purpose cleaning on bare concrete or painted floors. Thoroughly scrub the surface with a stiff bristle brush or broom. Wait 10-15 minutes to allow the Cleaner to lift stains from the surface. Wipe up excess Cleaner with rags or towels to keep the contaminants from spreading. Rinse thoroughly with fresh water. Repeat applications may be necessary for difficult stains. Remove excess water with a squeegee or mop.

STORAGE and DISPOSAL

Store at room temperature. Keep container closed when not in use. Dispose of container and/or unused contents in accordance with local, state, and federal regulations. Protect from freezing.

PHYSICAL PROPERTIES

		HEAVY DUTY DEGREASER
Composition		Surfactants and Water
Weight	Per Gallon	8.4 lbs.
	Per Liter	1.0 kg
Solids	By Weight	<5%
	By Volume	<5%
pH (as supplied)		013+
Volatile Organic Compounds		0 g/l
Shelf Life		NA
Flash Point		>200°F (93°C)
Safety Information		For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.



Rust-Oleum Canada
200 Confederation Parkway
Concord, ON, L4K 4T8

Phone: 800-387-3625
www.rustoleum.ca

Form: ARJ-2272
Rev.: 042522