



RUST-OLEUM® CHALKED DECORATIVE GLAZE

DESCRIPTION AND USES

Rust-Oleum® Chalked Decorative Glaze allows you to add a custom antiqued finish to any Chalked painted surface. This semi-transparent Decorative Glaze has good workability, allowing you to customize a handcrafted final look. Chalked Decorative Glaze enhances the details of brush strokes, wood grain, corners, crevices and more. Ideal for Chalked painted surfaces on wood, laminate, melamine or metal surfaces.

For interior use only.

PRODUCTS

236mL	DESCRIPTION
318242	Smoked Glaze
318243	Aged Glaze

PRODUCT APPLICATION

READ ALL DIRECTIONS BEFORE BEGINNING PROJECT

SURFACE PREPARATION

IMPORTANT! The Chalked Decorative Glaze must be applied over a clean, fully cured surface that has been painted with Rust-Oleum Chalked Paint. (Chalked Paint surface is fully cured in 3-4 days). To promote a high-end finish look, a cloth such as cheesecloth or a lint-free rag should be used to remove portions of the Chalked Decorative Glaze. Be sure to test glazing in a small area first before applying on the entire project.

PRODUCT APPLICATION (cont.)

APPLICATION

Use when temperature is between 10°C (50°F) and 35°C (95°F) and humidity is below 85% to ensure proper drying. Stir thoroughly to ensure any settled pigment is re-dispersed. Do not shake the can. Thinning is not required.

Using a 5cm (2") Rust-Oleum® Chalked synthetic brush, coat the surface with the Chalked Decorative Glaze. Be certain to apply the Decorative Glaze in all corners, crevices and raised panel sections. Using cheesecloth, wipe the surface (using varying pressure) to remove the Chalked Decorative Glaze to a desired look. If not satisfied with the appearance of the Decorative Glaze, while wet, lightly wipe the surface with a clean damp cloth and repeat the glazing process. On wood surfaces, wipe off in the direction of the wood grain.

DRY & RECOAT

Dry and recoat times are based on 21°C (70°F) and 50% relative humidity. Allow more time at cooler temperatures. Let dry a minimum of 8 hours before applying Rust-Oleum Chalked Matte Clear Protective Topcoat.

COVERAGE

Each 236mL will cover up to 4.6 m² (50 sq.ft)

CLEAN-UP

Clean brush and other application tools immediately with soap and water.

	TECHNICAL DATA	CHD-13
	RUST-OLEUM® CHALKED DECORATIVE GLAZE	

PHYSICAL PROPERTIES

		CHALKED DECORATIVE GLAZE
Resin Type		Acrylic
Pigment Type		Varies depending on colour
Solvents		Water and Propylene Glycol
Weight	Per Gallon	8.6-8.7lbs
	Per Liter	1.03-1.04 kg
Volatile Organic Compounds		<860 g/L (7.15 lbs/gal.)
Wet Film to Achieve DFT (Unthinned material)		Varies depending on surface type and porosity
Practical Coverage at Recommended DFT (assume 15% material loss)		4.6 m ² (37-50 sq ft.)
Dry Times at 21-27°C (70-80°F) and 50% Relative Humidity	Allow Base Coat to dry	2 hours
	Allow Chalked Glaze to dry	8 hours
Shelf Life		3 years
Flash Point		>93°C (200°F)
Safety Information		For additional information, see SDS

Calculated values are shown and may vary from the actual manufactured material.

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.