

	TECHNICAL DATA	SPC-07
• TRUSTED QUALITY SINCE 1921 • RUST-OLEUM® SPECIALTY	RUST-OLEUM® SPECIALTY FLUORESCENT SPRAYS	

DESCRIPTION AND USES

Rust-Oleum® Specialty Fluorescent Sprays provides bright, highly visible colour on a variety of surfaces. It is ideal for interior and exterior projects and also glows under a black light. For best results, apply over a white basecoat.

PRODUCTS

SKU	DESCRIPTION (340g Aerosol)
N1932830	Green
N1942830	Yellow
N1954830	Orange
N1955830	Red-Orange
N1959830	Pink

PRODUCT APPLICATION

Apply Outdoors. Apply when temperature is between 10-32°C (50-90°F) and humidity is below 65% to ensure proper drying. Avoid spraying in very windy or dusty conditions. Cover surrounding area to protect from overspray. Overspray can carry a significant distance.

SURFACE PREPARATION

Remove all dirt, grease, oil, salt and chemical contaminants by washing the surface with Krud Kutter® or a commercial detergent, or other suitable cleaning method. Rinse with fresh water and allow to thoroughly dry. Remove loose paint and rust with a wire brush or GATOR® sandpaper. Lightly sand glossy surfaces.

PRIMING

Use of a Zinsser® Primer provides excellent adhesion and hiding and is especially recommended for bare wood and metal. Apply an undercoat of white primer on darker surfaces for maximum brilliance.

APPLICATION

Shake can vigorously for one minute after the mixing ball begins to rattle. If mixing ball fails to rattle DO NOT STRIKE CAN. Contact Rust-Oleum. Hold can upright 20-25 cm (10-12") from surface and spray in a steady back and forth motion, slightly overlapping each stroke. Keep the same distance from the surface. Keep the can in motion while spraying. Apply 2 or more light coats a few minutes apart to avoid drips and runs. **Do not use near open flame.**

PRODUCT APPLICATION – cont'd

DRY & RECOAT

Dry and recoat times are based on 21°C (70°F) and 50% relative humidity. Allow more time at cooler temperatures. May recoat at anytime. Dries to the touch in 15 minutes, to handle in ½ hour. Fully dry in 24 hours. May top coat at anytime.

CLEAN-UP

When finished spraying, clear spray valve by turning can upside down and pushing spray button for 5 seconds. Clean up wet paint with xylene or mineral spirits. Throw away empty can in trash pick-up. Do not burn or place in home trash compactor.

CLOGGING

If the valve clogs, twist and pull off spray tip and rinse in a solvent such as mineral spirits. Do not insert any object into can valve opening

	TECHNICAL DATA	SPC-07
• TRUSTED QUALITY SINCE 1921 • RUST-OLEUM® SPECIALTY	RUST-OLEUM® SPECIALTY FLUORESCENT SPRAYS	

PHYSICAL PROPERTIES

		SPECIALTY FLUORESCENT SPRAYS
Resin Type		Modified Acrylic Lacquer
Pigment Type		Varies with colour
Solvents		Acetone, Hexane, Toluene, Xylene
MIR		1.30 Max
Fill Weight		312g (11oz)
Practical Coverage at Recommended DFT (assume 15% material loss)		Approximately 0.93 – 1.09 m ² / can (10-12 sq. ft./can)
Dry Times at 21-27°C (70-80°F) and 50% Relative Humidity	Touch	15 minutes
	Fully Dry	24 hours
	Recoat	Anytime
Dry Heat Resistance		93°C (200°F)
Shelf Life		5 years
Flash Point		-104°C (-156°F)
Safety Information		For additional information, see SDS

Calculated values are shown and may vary from the actual manufactured material.

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.