



SEAL-KRETE® MULTI-SURFACE WATER REPELLENT

DESCRIPTION AND USES

Seal-Krete® Multi-Surface Clear water repellent designed to provide protection for a variety of surfaces; water-based proprietary acrylic, low odor and low VOC.

Ideal for use on masonry, brick, stucco, concrete, pottery, stone, pressure-treated decks, plywood, pre-cast pavers, exposed aggregate, terrazzo and chattahoochee.

PRODUCT FEATURES

- Protects against water penetration
- Resists oil stains, salts and hot tire pick-up
- Extreme beading
- Non-yellowing

PRODUCT

| SKU | DESCRIPTION |
|--------|-------------|
| 323861 | 3.78L |

PRODUCT APPLICATION

READ ALL INSTRUCTIONS CAREFULLY BEFORE STARTING PROJECT

WEAR GLOVES AND SAFETY GLASSES

SURFACE PREPARATION

ALL SURFACES: Surface must be clean, dry and oil-free. Remove oil stains with a degreaser like EpoxyShield Oil Stain Remover. Make sure all curing compounds and releasing agents have been removed. Repair cracks and surface breaks. Cover windows, doors, etc., before application and use caution when applying on windy days.

BARE CONCRETE: Concrete must have cured for a minimum of 30 days. Etch smooth-finished concrete (such as basement or garage floors) with a concrete etching solution like Rustoleum 3 in 1 Clean-N-Etch.

Note: If etching with muriatic acid the area must be neutralized before proceeding.

PRODUCT APPLICATION (cont.)

APPLICATION

Read "LIMITATIONS" section before use. This sealer is ready-to-use; do not dilute. Invert jug 4-5 times to mix; do not shake (shaking can create air bubbles which affect finish). Apply one even coat with a garden sprayer or roller.

Note: Sealer goes on milky white but dries clear.

ROLLER: Dampen roller, remove excess water, then saturate roller with product. Keep a wet edge while rolling. Do not allow to puddle, foam or run. Apply with a 9 mm or 13 mm (3/8"-1/2") nap roller.

PUMP SPRAYER: Set at a fine spray and apply using a circular motion. To eliminate puddling or to achieve a more uniform finish, backroll immediately after spraying.

COVERAGE

14-28 m² per 3.78 L (150-300 ft² per gallon) (varies based on surface porosity). Apply one coat for dustproofing; two coats for a satin gloss finish. Second coat coverage is 50% greater.

DRY TIME

Dry to touch in 1 hour, recoat in 2 hours, allow foot traffic in 24 hours, vehicular traffic in 72 hours (25°C and 50% RH).

CLEAN-UP & STORAGE

Clean all tools immediately after use with soap and water. Store unused product in a dry place above 10°C (50°F). Do not use solvent-based cleaners on surface; clean occasionally with a mild soap and water solution. **KEEP FROM FREEZING.**

LIMITATIONS

Temperatures should be between 10-32°C and should not fall below 10°C within 24 hours of application. Do not apply if rain is expected within 12 hours. Do not use over acid-based stains or two part water-based or solvent-based epoxy coatings. Do not use on glazed tile. Do not use in areas subject to hydrostatic pressure. Smooth-finished concrete may be slippery when wet.



SEAL-KRETE® MULTI-SURFACE WATER REPELLENT

PHYSICAL PROPERTIES

| | | MULTI-SURFACE WATER REPELLENT |
|--|-----------------|---|
| Resin | | Acrylic |
| Pigment | | N/A |
| Solvent | | Glycol ethers |
| Weight | Per Gallon | 8.43 lbs. |
| | Per Liter | 1.01 kg |
| Solids | By Weight | 10% |
| | By Volume | 9% |
| Volatile Organic Compounds | | <218 g/l |
| Practical Coverage | | 14-28m ² /3.78L Coverage will vary depending on surface porosity and application method |
| Dry Times @ 25°C and 50% Relative Humidity | Touch | 1 hour |
| | Recoat | 2 hours |
| | Foot Traffic | 24 hours |
| | Vehicle Traffic | 72 hours |
| Shelf Life | | 2 years |
| Safety Information | | For additional information, see SDS |

Calculated values are shown and may vary from the actual manufactured material.

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.