



**DIF® GEL READY-TO-USE
WALLPAPER STRIPPER**

DESCRIPTION AND USES

Zinsser® DIF® Gel Ready-To-Use Wallpaper Stripper is an enzyme-based, non-toxic, no-drip, ready-to-use wallpaper stripper, which clings to the wallpaper, surface and stay wet longer. Removes Wallpaper, Decals, Con-Tact® Paper, Dried Glues & Adhesives.

It will effectively remove 7m² (75 sq. ft.) of wallpaper per 946 mL and 28m² (300 sq. ft.) per 3.78 L.

PRODUCT FEATURES

- Clings and stays wet longer
- Removes Wallpaper, Decals, Con-Tact® Paper, Dried Glues & Adhesives
- Non-staining
- Fast Acting; Low Odour; Clear; Fresh Scent
- Leaves wall clean

PRODUCTS

SKU	DESCRIPTION
Z02467H	946 mL (32 oz)
Z02441	3.78 L (1 gallon)

PRODUCT APPLICATION

READ ALL INSTRUCTIONS CAREFULLY BEFORE STARTING PROJECT

SURFACE PREPARATION

Spread a solvent resistant drop cloth covered with newspapers around the work area in case of drips and spills. Protect carpeting, furniture and porous ceilings before application. Protect eyes and skin. Wear safety goggles and chemical resistant gloves.

PRODUCT APPLICATION (cont.)

Note: Ensure good cross ventilation during application. Wear a NIOSH approved respirator when spraying.

APPLICATION

1. If top layer does not peel off easily, score with PaperTiger® to allow DIF to penetrate.
2. Spray on DIF. Shake before use. Protect adjacent areas from overspray. Wait 15-20 minutes.
3. Scrape off loose wallpaper with the Paper Scrapper™. To remove residual adhesive reapply DIF, wait 15-20 minutes, scrape or sponge off. Rinse with clean water.

TIP: If the top layer does not peel off easily, score (10 holes per square inch) with Paper Tiger™ and apply more DIF Gel Ready-To-Use Wallpaper Stripper. Allow DIF to penetrate for 15-20 additional minutes. Repeat the removal process and re-apply the stripper if necessary.

KEEP OUT OF REACH OF CHILDREN.

SPILLAGE

If spilled, contain spilled material and remove with an inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local and federal regulations. Clean up rags, papers and waste promptly.

CLEAN-UP

Clean up tools and equipment with soap and water.

DISPOSAL

To dispose of empty containers and unused product, contact your local environmental regulatory agency.

REGULATORY

CAUTION: Use only in a well ventilated area. Do not breathe vapours. May irritate eyes and skin. Do not get in eyes, on skin or clothing. **KEEP OUT OF REACH OF CHILDREN.**
FIRST AID TREATMENT: If breathed in, move person to fresh air. If swallowed call Poison Control Centre or doctor immediately. Do not induce vomiting. If in eyes or on skin, rinse well with water



TECHNICAL DATA

DIF® GEL READY-TO-USE WALLPAPER STRIPPER

PHYSICAL PROPERTIES

		GEL READY-TO-USE WALLPAPER STRIPPER
Composition		Acrylic Polymer, Disodium Ethylenediaminetetraacetate, Water
Weight	Per Gallon	8.3 lbs.
	Per Liter	1.00 kg
Volatile Organic Compounds		0 g/L
Practical Coverage		Varies with porosity of wallpaper. Strips approximately 7 m ² (75 ft ²)
Shelf Life		5 years
Flash Point		93°C (200°F)
Caution!		Avoid contact with eyes and skin. If eye contact occurs, flush with water for at least 15 minutes. If irritation persists, seek medical attention. Do not take internally. KEEP OUT OF REACH OF CHILDREN.
Safety Information		For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.