

ANTI-SKID ADDITIVE



DESCRIPTION

An aluminum oxide based anti-skid additive.

USES

The Anti-Skid Additive is designed to be added to epoxy, latex or oil based paints or stains to create a skid-resistant coating for concrete, wood, metal or fiberglass. Anti-Skid Additive will not change the performance or properties of the coatings when added at the recommended level.

APPEARANCE

Sandy particles.

PACKAGING

Carton containing 8 oz (227 g) of Aluminum oxide based powder.

MIXING

For one part floor coatings

Add one package for each gallon of coating just prior to application. Pour the additive in slowly, while stirring and mix thoroughly until the additive is evenly dispersed.

For two part floor coatings

Premix both components to re-disperse any settled particles, then add the activator to the base. If there is an induction time for the product, allow the coating to stand the recommended amount of time. Then pour the additive in slowly, while stirring and mix thoroughly until the additive is evenly dispersed.

APPLICATION

Apply the coating as normal. Remix the paint in the can periodically to ensure that any settled Anti-Skid Additive is reincorporated into the coating. If applying more than one coat of paint, mix the Epoxy Shield Anti-Skid Additive into the final coat only.

PHYSICAL PROPERTIES (Calculated values, may vary slightly from the actual manufactured material)

VOC (Volatile Organic Compounds)	NA
SOLIDS BY WEIGHT	100%
SOLIDS BY VOLUME	100%
MIXING RATIO	8 oz (227 g) per gallon of coating

SAFETY (For additional information, see MSDS)

FLASHPOINT	NA
LEAD-FREE	

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.