



RUST-OLEUM® ULTIMATE TURBO SPRAY SYSTEM™

DESCRIPTION AND USES

Rust-Oleum® Ultimate with Turbo Spray System™ will spray up to 10 inch (25 cm wide), which allows for faster project completion, making it ideal for large projects. This Ultimate formula provides the best possible corrosion protection with easy application, long lasting colour, gloss and durability. The speed and quality of professional spray equipment without the hassle. 4 times faster than traditional spray paints.

PRODUCTS

SKU	DESCRIPTION (Aerosol 656g)
352466	Ultimate Gloss White
352467	Ultimate Gloss Black

PRODUCT APPLICATION

READ ALL INSTRUCTIONS CAREFULLY BEFORE STARTING PROJECT

SURFACE PREPARATION

Remove all dirt, grease, oil, salt and chemical contaminants by washing the surface with Original Krud Kutter® Cleaner/Degreaser or other suitable cleaning method. Rinse with fresh water and allow to thoroughly dry. Remove loose paint and rust with a wire brush or sandpaper. Previously coated surfaces must be sound and in good condition. Smooth, hard, or glossy finishes should be scarified by sanding to create a surface profile.

WARNING! If you scrape, sand or remove old paint from any surface, you may release lead paint dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE; ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

APPLICATION

Use outdoors or in a well-ventilated area such as an open garage. Use when temperature is between 10°-32°C and humidity is below 65% to ensure proper drying. Do not apply to surfaces that, when heated, exceed 93°C or galvanized metal. Avoid spraying in very windy, dusty conditions. Cover surrounding area to protect from spray mist.

Shake can vigorously for one minute after mixing ball begins to rattle. If mixing ball fails to rattle DO NOT STRIKE CAN. Contact Rust-Oleum. Shake often during use. Hold can upright 25-35 cm from surface and spray in a steady back-and-forth motion, slightly overlapping each stroke. Keep the

can the same distance from the surface. Keep the can in motion while spraying. It is recommended to apply a light first coat, target 50% coverage. Apply 2 or more light coats a few minutes apart to avoid drips and runs.

PRODUCT APPLICATION (cont.)

DRY AND RECOAT TIMES

Based on 21°C and 50% relative humidity. Allow more time at cooler temperatures. Dries tack-free in 2-4 hours, to handle in 5-9 hours, and is fully dry in 24 hours. Apply a second coat or clear coat within 1 hour or after 24 hours.

CLEAN UP

Wipe off tip before storing. Clean up wet paint with xylene or mineral spirits. Properly discard empty container. Do not burn or place in home trash compactor.

CLOGGING

To clear spray for future use, turn can upside down and spray until clear gas is emitted. If valve clogs, twist and pull off spray tip and rinse it in a solvent such as mineral spirits. Do not stick a pin or other objects into the stem.



**RUST-OLEUM® ULTIMATE
WITH TURBO SPRAY SYSTEM™**

PHYSICAL PROPERTIES

		ULTIMATE WITH TURBO SPRAY SYSTEM
Resin Type		Oil modified Alkyd
Pigment Type		Varies depending on color
Solvents		Acetone, N-Butyl Acetate, Aromatic Hydrocarbons
MIR		1.40 max
Fill Weight		23 oz.
Recommended Dry Film Thickness (DFT) per Coat		1.0-2.0 mils (25-50µ)
Practical Coverage at Recommended DFT (assume 15% material loss)		24-40 sq.ft./can
Dry Times at 70°F (21°C) and 50% Relative Humidity	Touch	2-4 hours
	Handle	5-9 hours and fully dry in 24 hours
	Recoat	Within 1 hour or after 24 hours
Shelf Life		5 years
Flash Point		-141°F (-96°C)
Safety Information		For additional information, see SDS

Calculated values are shown and may vary from the actual manufactured material.

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.