

# KRUD KUTTER<sup>®</sup>

EARTH FRIENDLY

## OIL GRABBER<sup>®</sup>

**AMAZING  
PRODUCT!**

**ABSORBS & LIFTS  
EMBEDDED OIL STAINS  
WITHOUT SCRUBBING**

**Treats 1.6 m<sup>2</sup> (18 ft<sup>2</sup>) per 946 mL bottle!**

**OIL STAIN REMOVER  
IDEAL FOR ASPHALT, CONCRETE,  
MASONRY AND MORE!**



**ALSO REMOVES STAINS FROM:**

Anti-Freeze, Brake Fluid, Cooking Oils, Diesel Fluid, Grease, Hydraulic Fluid, Power Steering Fluid, Tar, Transmission Fluid, Tree Sap & Wax.

**SAFE, FAST & EFFECTIVE ON:**

Asphalt (Blacktop), Composite/Wood Decks, Concrete, Driveways, Garage Floors, Masonry, Patios, Pavers, Walkways, Wood & more!



Part Number	Unit Size	UPC Code	Case/Display	Carton Code
287781	236 mL	0-20066-29569-1	6 Unit Case	100-20066-30020-0
287779	946 mL	0-20066-29567-7	6 Unit Case	100-20066-30018-7



## Oil Grabber® Oil Stain Remover

REMOVES OIL STAINS  
FROM CONCRETE BEFORE  
PAINTING OR STAINING!

# 2014

## Technical Data

### Physical Data:

**Contains:** A proprietary blend of biodegradable surfactants, detergents, and emulsifiers, in a water based solution. No petroleum solvents, bleach or ammonia.

### Physical State:

Thick, pourable emulsion

**Colour:** White

**Odour:** Citrus

**pH:** 10-11

**Flash Point:** 72.4°C (162.4°F)

**VOC:** 4% (43.12g/L)

### Coverage:

236 mL: 0.4 m<sup>2</sup> (4.5 ft<sup>2</sup>)

946 mL: 1.6 m<sup>2</sup> (18 ft<sup>2</sup>)



**OUTPERFORMS TRADITIONAL LIQUID DEGREASERS.** Absorbs and lifts embedded oil stains, as it dries from liquid to powder.

Also removes stains from: Anti-Freeze, Brake Fluid, Cooking Oils, Diesel Fluid, Grease, Hydraulic Fluid, Power Steering Fluid, Tar, Transmission Fluid, Tree Sap & Wax. Use on: Asphalt (Blacktop), Concrete, Composite Decks, Driveways, Garage Floors, Masonry, Patios, Walkways, Wood & more.

**TREATS (UP TO) 1.6 m<sup>2</sup> PER 946 mL BOTTLE**

**IMPORTANT: SHAKE VIGOROUSLY FOR 60 SECONDS BEFORE USE.** Do not use on wet surfaces. May cause discolouration on sealed, coloured, or painted surfaces. Prior use of other cleaners may inhibit performance.

### DIRECTIONS:

1. Always test a small area before use.
2. For best results, use above 10°C (50°F), and provide maximum ventilation.
3. Scrape off buildup and sweep area.
4. Apply to stain, extending one inch beyond perimeter.
5. Allow 5 to 8 hours to dry. Sweep up powder.
6. Immediately rinse the area with a strong stream of water, and allow moisture to evaporate.
7. If stain remains, reapply, scrub with stiff-bristled brush, and repeat steps 5 and 6.

**CONTENTS MAY BE HARMFUL.** Do not swallow. Do not get in eyes or on skin or clothing. Do not breathe fumes. Keep out of reach of children. Wear rubber gloves and safety glasses. Use only in a well-ventilated area. **FIRST AID TREATMENT:** Contains C9-C11 alcohols ethoxylated. If swallowed, call a Poison Control Centre or doctor immediately. Do not induce vomiting. If in eyes or on skin, rinse well with water. If on clothes, remove clothes. If breathed in, move person into fresh air.

**RUST-OLEUM**  
CONSUMER BRANDS CANADA

Concord, Ontario L4K 4T8

© 2014 Rust-Oleum Corporation An RPM Company  
www.rustoleum.ca

1-800-387-3625