



**VARATHANE®
TOUCH-UP MARKERS**

DESCRIPTION AND USES

Varathane® Touch-Up Markers are a fast and easy way to touch up minor scratches on stained wood. Touch-Up Markers are suitable to repair minor scratches and blemishes on furniture, cabinets, moldings and floors. Use Varathane Touch-Up Markers for staining hard to reach areas or to provide colour highlights to arts and crafts.

PRODUCTS

SKU	DESCRIPTION (0.3 fl. oz.)
362582	Grey
362583	White

PRODUCT APPLICATION

SURFACE PREPARATION

Previously Stained Wood Surfaces - Remove any existing coatings using sandpaper or stripper. Prepare bare wood for staining by sanding in the direction of the grain. Begin with #120 grit sandpaper and progress through #150, #180 and #220 grits. Remove all sanding dust with a vacuum or clean rag dampened with mineral spirits. Soft woods such as pine, fir and maple require a wood conditioner.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

PRODUCT APPLICATION (cont.)

TESTING COLOUR

Be sure to test your marker to verify the desired colour. To test, apply stain in an inconspicuous area. When testing on soft woods, be sure to sand and condition the test area first.

APPLICATION

Shake well before using. Remove cap and slowly depress marker by pressing lightly on the tip. Press pen down and apply the stain to the wood. Quickly wipe off excess using a soft, lint-free cloth. Replace cap tightly after each use.

DRY TIME

Touch-Up Markers dry to the touch in 30 minutes and can be handled in 1 hour. Dry times may be affected by temperature, humidity and ventilation.

	TECHNICAL DATA	VAR-97
	VARATHANE® TOUCH-UP MARKERS	

PHYSICAL PROPERTIES

		TOUCH-UP MARKERS
Resin Type		Oil modified alkyd, vegetable oil
Pigment Type		Inorganic
Solvents		Mineral spirits
Weight	Per Gallon	7.9-8.1 lbs.
	Per Liter	0.95-0.97 kg
Solids	By Weight	43-45%
	By Volume	29-30%
Volatile Organic Compounds		<550
Practical Coverage		Varies with wood type
Dry Times at 25°C (77°F) and 50% Relative Humidity	Touch	45 minutes
	Recoat	1 hour
	Full Cure	1 hour
Shelf Life		5 years
Flash Point		41°C (106°F)
Safety Information		For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.