



TECHNICAL DATA

POPCORN CEILING TEXTURE WATERBASED AEROSOL

DESCRIPTION AND USES

Zinsser® Popcorn Ceiling Texture aerosol is designed to create a popcorn texture quickly and easily. This low-odour, waterbased formula creates professional results quickly. Popcorn Ceiling Texture aerosol is easy to apply and easy to clean. It is great for repairs and patches on already textured ceilings.

FEATURES

- Controlled spray
- Fast dry
- Repairs damaged texture
- Easy to apply, easy to clean

PRODUCTS

SKU	Description
317933	Bright White Popcorn Aerosol (396g)

PRODUCT APPLICATION

PAINTING CONDITIONS

Use in a well ventilated area. Use when temperature is between 10°C – 32°C (50°F – 90°F) and humidity is below 85% to ensure proper drying. Avoid spraying in very windy and dusty conditions. Cover surrounding area to protect from overspray.

SURFACE PREPARATION

Complete any necessary surface repairs. For best results, prime and seal the surface before painting.

PRODUCT APPLICATION (cont.)

TESTING SPRAY PATTERN

Practice spraying texture onto cardboard or scrap drywall to determine the best technique that delivers the desired pattern.

APPLICATION

Shake can vigorously for one minute before spraying. Also shake occasionally throughout use. Hold can upright 35 – 50 cm (14 – 20”) from surface and begin spraying in a quick back and forth motion that covers the surface and matches the surrounding texture. Keep the can in motion while spraying. Note: If the product output or pressure slows, shake the can and then continue the application. If problems still persist, put the can under running hot water to improve the spray performance.

Do not use near open flame.

DRY & RECOAT TIMES

Dry times are based on 21°C (70°F) and 50% relative humidity. Allow more time at cooler temperatures. Dries to the touch in 60 minutes and to recoat in 60 minutes. Allow to dry for 24 hours before topcoating. Heavier textures may take more time to dry.

CLEAN-UP

After use, turn can upside down and press spray nozzle until the spray mist is clear to prevent clogging. Wipe off tip before storing. Clean-up wet paint with water. Properly discard empty container. Do not burn or place in home trash compactor.

CLOGGING

If the valve clogs, twist and pull off spray tip and rinse it in water. Do not stick a pin or other objects into the valve stem.

KEEP OUT OF REACH OF CHILDREN.

REGULATORY

CONTAINER MAY EXPLODE IF HEATED. Do not puncture. Do not burn. Store away from heat.

**TECHNICAL DATA****POPCORN CEILING TEXTURE****PHYSICAL PROPERTIES**

		POPCORN CEILING TEXTURE WB AEROSOL
Resin Type		Ethylene-vinyl Acetate Copolymer
Pigment Type		Titanium Dioxide, Calcium Carbonate, Talc
Solvents		Dimethyl Ether, Water
MIR		0.1 Max
Fill Weight		396 g (14 oz)
Recommended Dry Film Thickness (DFT) per Coat		Varies depending on porosity and size of popcorn texture
Practical Coverage at Recommended DFT (assume 15% material loss)		Covers up to 0.5 m ² (5 sq.ft.) per can
Dry Times at 70-80°F (21-27°C) and 50% Relative Humidity	Touch	60 minutes
	Recoat	60 minutes
	Topcoat	24 hours
Shelf Life		2 years
Flash Point		-41°C (-42°F)
Safety Information		For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.